

## SOLID DOOR STAINLESS STEEL REFRIGERATOR



- Superior build quality & energy efficient
- Stainless Steel Exterior & Interior
- Electronic thermostat and digital LED temperature display
- High quality efficient refrigeration system
- Locking self-closing doors with semi recessed ergonomic handles
- Heavy-duty polyethylene coated adjustable wire shelves
- Lock & Key Standard
- Come with casters installed
- Temperature range 33 to 40°F / 0.5 to 4°C

| MODEL      | Cabinet Dimensions (inches) |       |       | VOLTAGE   | RUN AMPS | FUSE AMPS | SHELVES | STORAGE CAPACITY Cu-ft | SHIPPING WEIGHT (LBS) | PLUG TYPE (NEMA) |
|------------|-----------------------------|-------|-------|-----------|----------|-----------|---------|------------------------|-----------------------|------------------|
|            | L                           | D     | H     |           |          |           |         |                        |                       |                  |
| BSD-1R-HC  | 27                          | 32.75 | 80.8* | 115/60/1  | 3        | 15        | 3       | 23                     | 350                   | 5-15P            |
| BSD-2NR-HC | 39.5                        | 32.75 | 80.8* | 115/60/1  | 4.5      | 15        | 6       | 35                     | 460                   | 5-15P            |
| BSD-2R-HC  | 54                          | 32.75 | 80.8* | 115/60/1  | 4.5      | 15        | 6       | 49                     | 518                   | 5-15P            |
| BSD-3R-HC  | 81                          | 32.75 | 80.8* | 115/ 60/1 | 7.5      | 15        | 9       | 72                     | 669                   | 5-15P            |

These merchandisers are designed for use in stores when temperature and humidity do not exceed 75°F and 55% R.H. Coldco reserves the right to change or revise specifications and product design in connection with any feature of our products without notice. Units are completely pre-wired at the factory with plug and are ready for final connection to a single phase dedicated circuit. \*Height includes casters.

